

Item # ADS-943GC, Sampling A/D Converters

List Price

Sampling A/D Converters

14 Bit, 3MHz (3MSPS), Sampling Analog to Digital (A/D) Converter, $\pm 2V$ Input range, $0^{\circ}C$ to $+70^{\circ}C$ temperature range, surface mount package.



Image is for illustration purposes only

SPECIFICATIONS

| | |
|--|--------------|
| Resolution | 14 bits |
| Number of Channels | 1 |
| Sampling Rate | 3 MHz |
| Power Consumption | 1.8 W |
| Differential Non-Linearity Error/Other | 0.5 LSB |
| Integral Non-Linearity Error/Other | 0.75 LSB |
| Package Type | SMT |
| Input Range 1st (min) | -2 V |
| Input Range 1st (max) | 2 V |
| Required Supply Voltage 1st | 5 V |
| Required Supply Voltage 2nd | -5 V |
| Total Harmonic Distortion | -83 dB |
| Signal to Noise Ratio | 79 dB |
| Analog Bandwidth | 30 MHz |
| Operating Temp. Range (min) | $0^{\circ}C$ |

| | |
|-----------------------------|----------------------------|
| Operating Temp. Range (max) | 70 °C |
| RoHS | No |
| Status | Recommended for new design |